

XL GRIP (E3) - Tekniska specifikationer



Description

XL GRIP (E-3) är ett diagonaldäck för dumprar. Det är utformat för att vara extra motståndskraftigt mot skärskador och punkteringar under hårda förhållanden där exceptionell dragkraft krävs. Dessa egenskaper ger däckets en längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Stel dumper

Version	STANDARD
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94015689
Ply Rating	28
Overall Width (inch)	18.3
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	173
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	83	109
30	14800	-
5	-	25400

Printed on 4/27/2024 5:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..