

## XL GRIP (G3) - Tekniska specifikationer



### Description

XL GRIP (G-3) är ett diagonaldäck för väghyvlar. Det är utformat för att vara extra motståndskraftigt mot skärskador och punkteringar i tuffa hyvlingsmiljöer där exceptionell dragkraft krävs.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Väghyvlare

Version	STANDARD
Type	TL
Tyre Size	16.00 - 24 (-)

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	432
Overall Diameter (mm)	1450
Static Loaded Radius (mm)	654
Rolling Circumference (mm)	4289
SRI (mm)	-
Rim Rec	10.00 VA SDC
Rim Alt	-
TRA Code	G3

## Load capacity (Kg)

km/h / bar	3.00
40	4500

Printed on 4/27/2024 11:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..