

XL GRIP IND3 (RTG) - Tekniska specifikationer



Description

XL GRIP (IND-3) är ett däck med vinkelskikt för RTG-kranar som används till staplings- och lyftarbeten. Däcket har ett robust hölje tillverkat med en specialkomponerad gummiblandning för extra lång livslängd.

UM

International Standard

Construction

 BIAS

Machinery

Industri: RTG-kran

Version	INDUSTRIAL
Type	TL
Tyre Size	24.00 - 29

Dimensions International Standard

Ply Rating	42
Overall Width (mm)	656
Overall Diameter (mm)	1994
Static Loaded Radius (mm)	900
Rolling Circumference (mm)	5860
Rim Rec	17.00/3.5
TRA Code	IND3

Load capacity (Kg)

	km/h / bar	9.00
	10	36260
	25	33575

Printed on 5/3/2024 2:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..