XL GRIP PLUS - Tekniska specifikationer

Description

XL GRIP PLUS (L-4) är specialtillverkat för hjullastare. Det djupa mönstret ger ett däck som är mycket skär- och punkteringsbeständigt och har längre livslängd. XL GRIP PLUS lämpar sig särskilt väl för tung användning.

UM

International Standard

Construction

BIAS

Machinery

OTR: Bulldozer • Hjullastare

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	690
Overall Diameter (mm)	1775
Static Loaded Radius (mm)	815
Rolling Circumference (mm)	5253
Rim Rec	22.00/3.0
TRA Code	L4

Load capacity (Kg)

km/h / bar	4.75
10	15500

Printed on 5/3/2024 11:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..