

## XL GRIP PLUS - Tekniska specifikationer



### Description

XL GRIP PLUS (L-4) är specialtillverkat för hjullastare. Det djupa mönstret ger ett däck som är mycket skär- och punkteringsbeständigt och har längre livslängd. XL GRIP PLUS lämpar sig särskilt väl för tung användning.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Bulldozer • Hjullastare

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

## Dimensions International Standard

<b>Ply Rating</b>	32
<b>Overall Width (mm)</b>	690
<b>Overall Diameter (mm)</b>	1775
<b>Static Loaded Radius (mm)</b>	815
<b>Rolling Circumference (mm)</b>	5253
<b>Rim Rec</b>	22.00/3.0
<b>TRA Code</b>	L4

## Load capacity (Kg)

km/h / bar	5.50
10	17000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/6/2024 5:45 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..