

## EARTHMAX SR 315 CS - Veri Sayfasını İndir



### Description

EARTHMAX SR 315 CS L-3S, madencilik operasyonlarında zincirli yükleyicilerin ön aksları için özel olarak tasarlanmış Tamamen Çelik bir radyal lastiktir.

Pahlı Omuz (Chamfered Shoulder; CS) ile özel sırt konturu, lastik zincirlerinin omuz bölgesi de dahil olmak üzere sırt yüzeyi boyunca daha iyi oturmasını sağlar.

Zincir uygulamasından sonraki Genel Çap, ön ve arka lastiklerin yakın eşleşmesi için arka aksa takılan BKT EARTHMAX SR 55 L-5S ile uyumludur.

EARTHMAX SR 315 CS, LHD'ler (Yeraltı Yük Taşıma Damperi) ve yükleyicilerle kazma işlemleri sırasında ön lastik hasarı riskini ortadan kaldırmak için tasarlanmıştır.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Yük taşıma damperi (LHD) • Yükleyici

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
<b>29.5 R 29</b>	CUT RESISTANT COMPOUND	94069378	L3S	**	218 A2	25.00/3.5	24.00/3.5	30.7	74.4	33.1	225	TL
<b>35/65 R 33</b>	CUT RESISTANT COMPOUND	94070992	L3S	***	229 A2	28.00/3.5	-	34.6	76.7	34.1	231.7	TL
<b>35/65 R 33</b>	CUT RESISTANT COMPOUND	94069385	L3S	**	224 A2	28.00/3.5	-	34.6	76.7	34.1	231.7	TL

Printed on 4/17/2024 5:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..