

AGRI TRAILER - Teknik Özellikler



Description

AGRI TRAILER özellikle traktör römorkları için tasarlanmıştır. Modern çiftçilik için ideal lastiktir ve hem yolda hem de yol dışında taşıma uygulamaları için uygundur. Sağlam yapısı sayesinde yüksek yük kapasitesine sahiptir ve ekstra derin sırtı yakıttan tasarruf ve daha uzun kullanım ömrü sağlar.

UM

International Standard

Construction



Machinery

Zirai: Römork

Version	STANDARD
Туре	ΤΤ
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	286
Overall Diameter (mm)	1080
Rim Rec	7.5
Rim Alt	7.0;8.0

Load capacity (Kg)

km/h / bar	9.30	8.60
30 LS	3845	-
30 LD	-	3405

Printed on 4/19/2024 10:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..