AGRIMAX ELOS - Teknik Özellikler

Description

AGRIMAX ELOS çeltik tarlaları ve bataklıklar gibi ıslak arazilerde karşılaşılan, en zorlu çalışma koşullarında bile üstün çekiş performansını artırmak üzere tasarlanmıştır. Sırt dişlerinin tasarımı, taşıma işlemleri sırasında ve çamurlu arazilerdeki faaliyetlerde elzem olan, en yüksek kendini temizleme niteliklerini sağlamak için özel olarak geliştirilmiştir. Makinelerin çalışmama sürelerini azaltarak çiftçilerin verimliliğini en üst düzeye çıkarmak için, AGRIMAX ELOS'a yanak koruyucuları entegre edilerek her durumdaki olası zararlara karşı maksimum koruma sağlanmıştır.

UM

US Standard

Construction

RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	340/85 R 38 (13.6 R 38)
LI/SS	133 A8/B

Dimensions US Standard

Usa code	94040452
Section Width (inch)	13.9
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.9
Rolling Circumference (inch)	188
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-001477
TRA Code	R2

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2500	2910	3320	3730	4130	4540
25	2500	2910	3320	3730	4130	4540
20	2680	3120	3550	3990	4430	4860
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2680	3120	3550	3990	4430	4860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..