

## AGRIMAX ELOS - Teknik Özellikler



### Description

AGRIMAX ELOS çeltik tarlaları ve bataklıklar gibi ıslak arazilerde karşılaşılan, en zorlu çalışma koşullarında bile üstün çekiş performansını artırmak üzere tasarlanmıştır. Sırt dişlerinin tasarımı, taşıma işlemleri sırasında ve çamurlu arazilerdeki faaliyetlerde elzem olan, en yüksek kendini temizleme niteliklerini sağlamak için özel olarak geliştirilmiştir. Makinelerin çalışmama sürelerini azaltarak çiftçilerin verimliliğini en üst düzeye çıkarmak için, AGRIMAX ELOS'a yanak koruyucuları entegre edilerek her durumdaki olası zararlara karşı maksimum koruma sağlanmıştır.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Traktör

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 480/80 R 42<br>(18.4 R 42) |
| LI/SS     | 151 A8/B                   |

## Dimensions International Standard

|                            |                  |
|----------------------------|------------------|
| Section Width (mm)         | 489              |
| Overall Diameter (mm)      | 1890             |
| Static Loaded Radius (mm)  | 857              |
| Rolling Circumference (mm) | 5629             |
| SRI (mm)                   | 875              |
| Rim Rec                    | DW 16 L          |
| Rim Alt                    | DD 16 L ; W 16 L |
| ECE                        | E4-106R-001481   |
| TRA Code                   | R2               |

## Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1900 | 2210 | 2520 | 2830 | 3140 | 3450 |
| 40         | 1900 | 2210 | 2520 | 2830 | 3140 | 3450 |
| 30         | 2035 | 2365 | 2700 | 3030 | 3365 | 3695 |
| 10 LT      | 2545 | 2960 | 3380 | 3795 | 4210 | 4625 |
| 10 HT      | 2035 | 2365 | 2700 | 3030 | 3365 | 3695 |

Printed on 4/24/2024 9:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..