

AGRIMAX FORCE - Teknik Özellikler



Description

BKT'nin lüks ürünü AGRIMAX FORCE, yüksek güçlü traktörler ve biçerdöverlerle toprak işleme, taşıma ve hasat uygulamaları için özel olarak tasarlanmış, üstün performans ve verimlilik sağlayan radyal bir lastiktir. IF teknolojisi sayesinde, bu lastik, standart bir lastiğe kıyasla daha düşük bir şişirme basıncıyla ağır yükler taşıyarak toprak sıkışmasını azaltır. AGRIMAX FORCE, güçlendirilmiş bir damağa sahiptir ve konforlu bir sürüş deneyimine ek olarak gelişmiş çekiş, üstün kendi kendini temizleme özellikleri ve yakıt ekonomisi sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Biçerdöver • Yüksek güçte traktör

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | IF 380/80 R 38 |
| LI/SS | 149 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94062140 |
| Section Width (inch) | 15 |
| Overall Diameter (inch) | 61.9 |
| Static Loaded Radius (inch) | 28.5 |
| Rolling Circumference (inch) | 188.7 |
| Rim Rec | W 12 |
| Rim Alt | W 11 ; W 13 |
| ECE | E11-106R-005715 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-------------------------------|------|------|------|------|------|------|------|-------|
| 45 | 3050 | 3520 | 4030 | 4560 | 5080 | 5600 | 6130 | 6510 |
| From 40 to 25 | 3360 | 3870 | 4440 | 5020 | 5590 | 6160 | 6730 | 7165 |
| 20 | 3490 | 4020 | 4620 | 5210 | 5810 | 6400 | 7000 | 7450 |
| 12 | 3630 | 4180 | 4790 | 5410 | 6030 | 6650 | 7260 | 7740 |
| 5 | 4270 | 4910 | 5630 | 6360 | 7090 | 7810 | 8540 | 9090 |
| *Upto 5 Cyc with front loader | 4710 | 5410 | 6220 | 7020 | 7810 | 8620 | 9420 | 10030 |
| 5HT | 3490 | 4020 | 4620 | 5210 | 5810 | 6400 | 7000 | 7450 |

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 4/27/2024 6:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..