

AGRIMAX RI 818 - Teknik Özellikler



Description

AGRIMAX RI 818, sulama uygulamaları ile ilaçlama ve sulama makineleri için tasarlanan bir radyal lastiktir. Özel olarak tasarlanan sırt deseni, ıslak ve çamurlu ortamlarda olağanüstü kendi kendini temizleme özelliklerine ek olarak mükemmel çekiş sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama ve sulama makinesi

Version	STANDARD
Type	TL
Tyre Size	280/85 R 24 (11.2 R 24)
LI/SS	140

Dimensions International Standard

Section Width (mm)	287
Overall Diameter (mm)	1086
Static Loaded Radius (mm)	490
Rolling Circumference (mm)	3271
SRI (mm)	525
Rim Rec	W 10
Rim Alt	W 9

Load capacity (Kg)

km/h / bar	1.6
CREEP	2500

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN) / For CREEP loads inflation pressure to be increased by +6 psi

Printed on 4/25/2024 12:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..