

AGRIMAX RT 600 - Teknik Özellikler

Description

AGRIMAX RT 600; çim saha, hasat ve yayma uygulamaları için ideal bir lastiktir. Geniş temas alanı sayesinde AGRIMAX RT 600, arazide mükemmel bir basınç dağılımı sağlayarak çim sahadaki hasarı azaltır ve toprağınızı korur. Yuvarlak omuz teknolojisi, güçlendirilmiş damak ve daha yüksek diş sayısı sayesinde mükemmel sabitleme ve çekiş sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Biçerdöver • Yayıcı • Traktör



Version	STANDARD
Type	TL
Tyre Size	900/60 R 32
LI/SS	181 A8/178 B

Dimensions International Standard

Section Width (mm)	896
Overall Diameter (mm)	1893
Static Loaded Radius (mm)	841
Rolling Circumference (mm)	5697
SRI (mm)	900
Rim Rec	DW 27 B
Rim Alt	DW 28 B ; DW 30 B
ECE	E11-106R-005768

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	3375	3825	4350	4800	5325	5925	6375	6975	7500	-	-
40	3715	4210	4785	5280	5860	6520	7015	7675	8250	-	-
30	3975	4505	5125	5655	6270	6980	7510	8215	8830	-	-
10 LT	4975	5640	6415	7080	7850	8735	9400	10285	11055	-	-
10 HT	3975	4505	5125	5655	6270	6980	7510	8215	8830	-	-
10 Cyc.	-	6765	7690	8485	9415	10475	11270	12330	13255	13465	14025

Printed on 4/23/2024 9:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..