

AGRIMAX RT 657 - Teknik Özellikler



Description

AGRIMAX RT 657 yol üzerinde kullanım ve toprak işleme için ideal lastiktir; bazı ebatlar üzüm hasadı için de uygundur. Bu lastik, mükemmel sürüş konforunun yanı sıra önemli ölçüde yakıt tasarrufu da sağlar. Yüksek hız seviyelerinde de yüksek yük kapasitesine sahiptir. AGRIMAX RT 657, performanstan ödün vermeden çok yönlü ve güvenilir bir lastiğe ihtiyaç duyanlar için en iyi seçimdir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	540/65 R 24
LI/SS	146 D/149 A8

Dimensions US Standard

Usa code	94028658
Section Width (inch)	20.9
Overall Diameter (inch)	51.7
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	154.7
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000773
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3170	3700	4170	4630	5090	5490	6080	6600
30	3340	3890	4380	4860	5360	5760	6390	6940
25	3440	4010	4520	5020	5520	5950	6590	7160
20	3660	4270	4790	5320	5860	6320	7000	7610
5 LT	4250	4970	5590	6210	6830	7360	8160	8860
5 HT	3660	4270	4790	5320	5860	6320	7000	7610

Printed on 4/24/2024 11:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..