

## AGRIMAX RT 765 - Teknik Özellikler



### Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	280/70 R 16
LI/SS	112 A8/B

## Dimensions International Standard

Section Width (mm)	282
Overall Diameter (mm)	798
Static Loaded Radius (mm)	356
Rolling Circumference (mm)	2370
SRI (mm)	390
Rim Rec	W 9
Rim Alt	W 8 ; W 8 L ; W 10
ECE	E4-106R-000633
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	530	605	695	785	875	965	1045	1120
40	530	605	695	785	875	965	1045	1120
30	565	650	745	840	940	1035	1120	1200
10 LT	710	815	935	1055	1175	1295	1400	1505
10 HT	565	650	745	840	940	1035	1120	1200

Printed on 4/26/2024 9:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..