

AGRIMAX RT 765 - Teknik Özellikler



Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	280/70 R 18
LI/SS	114 A8/B

Dimensions International Standard

Section Width (mm)	282
Overall Diameter (mm)	849
Static Loaded Radius (mm)	381
Rolling Circumference (mm)	2547
SRI (mm)	410
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000635
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1100	1180
40	555	640	735	830	925	1015	1100	1180
30	595	685	785	890	990	1090	1180	1265
10 LT	745	860	985	1110	1240	1365	1475	1585
10 HT	595	685	785	890	990	1090	1180	1265

Printed on 4/26/2024 5:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..