

## AGRIMAX RT 765 - Teknik Özellikler



### Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	SPECIAL
Type	TL
Tyre Size	380/70 R 24
LI/SS	125 D

## Dimensions International Standard

TKPH	1
Section Width (mm)	380
Overall Diameter (mm)	1190
Static Loaded Radius (mm)	538
Rolling Circumference (mm)	3560
SRI (mm)	550
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E11-106R-005767
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	910	1060	1205	1355	1505	1650
50	955	1115	1270	1425	1580	1735
40	1000	1160	1325	1485	1650	1810
30	1045	1220	1390	1560	1730	1900
10 LT	1220	1420	1620	1820	2020	2215
10 HT	1045	1220	1390	1560	1730	1900

Printed on 4/26/2024 7:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..