

AGRIMAX RT 765 - Teknik Özellikler



Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	480/70 R 28
LI/SS	140 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1421
Static Loaded Radius (mm)	634
Rolling Circumference (mm)	4185
SRI (mm)	650
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005521
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1375	1600	1825	2050	2275	2500
50	1445	1680	1920	2155	2390	2625
40	1510	1755	2005	2250	2495	2740
30	1585	1840	2100	2360	2620	2875
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1585	1840	2100	2360	2620	2875

Printed on 4/26/2024 6:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..