

## AGRIMAX RT 765 - Teknik Özellikler



### Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	SPECIAL
Type	TL
Tyre Size	480/70 R 38
LI/SS	145 D

## Dimensions US Standard

Usa code	94063208
Section Width (inch)	18.9
Overall Diameter (inch)	66.2
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	199
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005832
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	3520	4100	4670	5250	5820	6390
30	3690	4300	4910	5510	6120	6710
25	3860	4500	5130	5750	6380	7010
20	4050	4710	5370	6030	6690	7350
5 LT	4720	5790	6260	7030	7800	8580
5 HT	4050	4710	5370	6030	6690	7350

Printed on 4/26/2024 12:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..