

## AGRIMAX RT 765 - Teknik Özellikler



### Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	600/70 R 28
LI/SS	157 D

## Dimensions US Standard

Usa code	94067251
Section Width (inch)	23.3
Overall Diameter (inch)	61.1
Static Loaded Radius (inch)	27.4
Rolling Circumference (inch)	184.7
Rim Rec	DW 18 L
Rim Alt	DW 20 B
ECE	E11-106R-006861
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4280	4920	5640	6370	7100	7830	8550	9090
30	4500	5170	5930	6690	7460	8220	8980	9560
25	4680	5390	6180	6980	7780	8580	9370	9960
15	4930	5650	6490	7330	8170	9010	9840	10460
5 LT	5730	6590	7560	8540	9510	10490	11460	12190
5 HT	4930	5650	6490	7330	8170	9010	9840	10460

Printed on 4/26/2024 5:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..