

AGRIMAX RT 765 - Teknik Özellikler



Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	620/70 R 42
LI/SS	160 D

Dimensions US Standard

Usa code	94063116
Section Width (inch)	24.6
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	34.5
Rolling Circumference (inch)	226.1
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-005835
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	5460	6350	7240	8130	9030	9920
30	5730	6670	7610	8540	9480	10420
25	5990	6970	7940	8920	9900	10870
20	6280	7310	8330	9360	10380	11410
5 LT	7320	8510	9710	10900	12100	13290
5 HT	6280	7310	8330	9360	10380	11410

Printed on 4/26/2024 10:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..