

AGRIMAX RT 855 - Teknik Özellikler



Description

AGRIMAX RT 855 mükemmel çekiş ve konfor özellikleri sunar. Temel olarak toprak işleme ve hem arazi hem de kara yolu taşımacılığı için tasarlanan lastikte bazı ebatlar, ilaçlama ve üzüm hasadı için de uygundur. AGRIMAX RT 855, arazi operasyonlarından yol kullanımına hızlı bir geçiş sağlayan mükemmel kendi kendini temizleme özelliklerine sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	SPECIAL
Type	TL
Tyre Size	250/85 R 22
LI/SS	113 A8/B

Dimensions International Standard

TKPH	1
Section Width (mm)	251
Overall Diameter (mm)	985
Static Loaded Radius (mm)	453
Rolling Circumference (mm)	2964
SRI (mm)	475
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-002973
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	545	625	715	805	900	990	1070	1150
40	545	625	715	805	900	990	1070	1150
30	585	670	770	865	965	1065	1150	1235
10 LT	730	835	960	1085	1210	1330	1440	1545
10 HT	585	670	770	865	965	1065	1150	1235

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/12/2025 7:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..