

## AGRIMAX RT 855 - Teknik Özellikler



### Description

AGRIMAX RT 855 mükemmel çekiş ve konfor özellikleri sunar. Temel olarak toprak işleme ve hem arazi hem de kara yolu taşımacılığı için tasarlanan lastikte bazı ebatlar, ilaçlama ve üzüm hasadı için de uygundur. AGRIMAX RT 855, arazi operasyonlarından yol kullanımına hızlı bir geçiş sağlayan mükemmel kendi kendini temizleme özelliklerine sahiptir.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 280/85 R 28<br>(11.2 R 28) |
| LI/SS     | 118 A8/B                   |

Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94021543       |
| Section Width (inch)         | 11.5           |
| Overall Diameter (inch)      | 46.7           |
| Static Loaded Radius (inch)  | 21.5           |
| Rolling Circumference (inch) | 140.1          |
| Rim Rec                      | W 10           |
| Rim Alt                      | W 9            |
| ECE                          | E4-106R-000614 |
| TRA Code                     | R1W            |

Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 1610 | 1860 | 2130 | 2390 | 2660 | 2910 |
| 25        | 1610 | 1860 | 2130 | 2390 | 2660 | 2910 |
| 20        | 1720 | 2010 | 2280 | 2570 | 2840 | 3120 |
| 5 LT      | 2150 | 2500 | 2850 | 3210 | 2560 | 3900 |
| 5 HT      | 1720 | 2010 | 2280 | 2570 | 2840 | 3120 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/12/2025 9:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..