

AGRIMAX RT 945 - Teknik Özellikler



Description

AGRIMAX RT 945 özellikle ürün arası için tasarlanmıştır: Ürünlere zarar vermez ve verimi korur. Mükemmel kendi kendini temizleme özellikleri, AGRIMAX RT 945'in mükemmel performans gösterdiği arazi operasyonlarından yol kullanımına hızlı bir geçiş sağlar. Güçlü gövdesi, lastiğe mükemmel sabitleme, olağanüstü çekiş ve sıra dışı dayanıklılık sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Traktör

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 380/90 R 54 (14.9 R 54) |
| LI/SS | 158 A8/B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 380 |
| Overall Diameter (mm) | 2056 |
| Static Loaded Radius (mm) | 962 |
| Rolling Circumference (mm) | 6232 |
| SRI (mm) | 975 |
| Rim Rec | W 12 |
| Rim Alt | W 11 ; W 13 |
| ECE | E4-106R-001488 |
| TRA Code | R1W |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 |
|------------|------|------|------|------|------|------|------|------|
| 50 | 1955 | 2510 | 3060 | 3315 | 3615 | 3955 | 4250 | - |
| 40 | 1955 | 2510 | 3060 | 3315 | 3615 | 3955 | 4250 | - |
| 30 | 2095 | 2685 | 3280 | 3550 | 3870 | 4235 | 4550 | - |
| 10 | 2295 | 3000 | 3635 | 4335 | 4975 | 5165 | 5740 | 6375 |

Printed on 4/26/2024 11:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..