

AGRIMAX RT 955 - Teknik Özellikler



Description

AGRIMAX RT 955, ürün arası uygulamalarına yönelik bir BKT radyal lastiktir; bazı ebatlar ilaçlama ve üzüm bağları için de uygundur. Yuvarlak omuzlu özel sırt tasarımı mükemmel çekiş performansı, sabitleme ve kendi kendini temizleme özellikleri sağlar. Güçlü gövdesi sayesinde AGRIMAX RT 955, yüksek yük kapasitesine sahiptir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	230/95 R 32 (9.5 R 32)
LI/SS	128 A8/B

Dimensions US Standard

Usa code	94026678
Section Width (inch)	9
Overall Diameter (inch)	49.3
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	150
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000764
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1550	2030	2470	2700	2870	3140	3420	3690	3960	-
25	1550	2030	2470	2700	2870	3140	3420	3690	3960	-
20	1660	2170	2650	2900	3060	3360	3660	3960	4250	-
5	1850	2330	2870	3390	3940	4060	4530	5000	5480	5950

Printed on 2/26/2024 11:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..