

## AGRIMAX RT 955 - Teknik Özellikler



### Description

AGRIMAX RT 955, ürün arası uygulamalarına yönelik bir BKT radyal lastiktir; bazı ebatlar ilaçlama ve üzüm bağları için de uygundur. Yuvarlak omuzlu özel sırt tasarımı mükemmel çekiş performansı, sabitleme ve kendi kendini temizleme özellikleri sağlar. Güçlü gövdesi sayesinde AGRIMAX RT 955, yüksek yük kapasitesine sahiptir.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: İlaçlama • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	230/95 R 40 (9.5 R 40)
LI/SS	132 A8/B

## Dimensions US Standard

Usa code	94055210
Section Width (inch)	9
Overall Diameter (inch)	57.2
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	175
Rim Rec	W 7
Rim Alt	W 8
ECE	E11-106R-004066
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1810	2340	2820	3130	3310	3620	3920	4190	4410	-
25	1810	2340	2820	3130	3310	3620	3920	4190	4410	-
20	1940	2500	3020	3350	3540	3870	4200	4490	4720	-
5	2050	2580	3170	3770	4360	4500	5030	5560	6080	6610

Printed on 2/26/2024 12:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..