

AGRIMAX RT 955 - Teknik Özellikler



Description

AGRIMAX RT 955, ürün arası uygulamalarına yönelik bir BKT radyal lastiktir; bazı ebatlar ilaçlama ve üzüm bağları için de uygundur. Yuvarlak omuzlu özel sırt tasarımı mükemmel çekiş performansı, sabitleme ve kendi kendini temizleme özellikleri sağlar. Güçlü gövdesi sayesinde AGRIMAX RT 955, yüksek yük kapasitesine sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	270/95 R 44 (11.2 R 44)
LI/SS	142 A8/B

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1632
Static Loaded Radius (mm)	764
Rolling Circumference (mm)	4983
SRI (mm)	775
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-00784
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1035	1355	1645	1805	1910	2095	2280	2465	2650	-
40	1035	1355	1645	1805	1910	2095	2280	2465	2650	-
30	1110	1450	1765	1935	2045	2245	2445	2645	2840	-
10	1235	1555	1910	2270	2625	2705	3025	3340	3660	3975

Printed on 2/26/2024 12:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..