

## AGRIMAX RT 955 - Teknik Özellikler



### Description

AGRIMAX RT 955, ürün arası uygulamalarına yönelik bir BKT radyal lastiktir; bazı ebatlar ilaçlama ve üzüm bağları için de uygundur. Yuvarlak omuzlu özel sırt tasarımı mükemmel çekiş performansı, sabitleme ve kendi kendini temizleme özellikleri sağlar. Güçlü gövdesi sayesinde AGRIMAX RT 955, yüksek yük kapasitesine sahiptir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: İlaçlama • Üzüm hasat makinesi

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 340/85 R 48<br>(13.6 R 48) |
| LI/SS     | 152 A8/B                   |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 353            |
| Overall Diameter (mm)      | 1797           |
| Static Loaded Radius (mm)  | 855            |
| Rolling Circumference (mm) | 5572           |
| SRI (mm)                   | 875            |
| Rim Rec                    | W 12           |
| Rim Alt                    | W 11           |
| ECE                        | E4-106R-000800 |
| TRA Code                   | R1             |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50         | 1385 | 1815 | 2205 | 2415 | 2560 | 2805 | 3055 | 3305 | 3550 | -    |
| 40         | 1385 | 1815 | 2205 | 2415 | 2560 | 2805 | 3055 | 3305 | 3550 | -    |
| 30         | 1485 | 1940 | 2360 | 2585 | 2740 | 3005 | 3270 | 3535 | 3800 | -    |
| 10         | 1655 | 2080 | 2560 | 3040 | 3515 | 3625 | 4050 | 4475 | 4900 | 5325 |

Printed on 2/26/2024 12:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..