AGRIMAX SIRIO - Teknik Özellikler

Description

AGRIMAX SIRIO, BKT tarafından yüksek performanslı traktörler için geliştirilmiş yüksek hızlı bir lastiktir (70 km/sa. - 45 mil/sa. hıza kadar). Tasarımı, hem taşıma hem de toprak işleme uygulamaları için mükemmeldir. Yüksek yanak esnekliği, sürüş deneyimini iyileştirmek için olağanüstü sabitleme, kullanım ve konfor sağlar. Ağır yükleri düşük bir şişirme basıncında taşımayı sağlayan IF teknolojisine sahip versiyonlar da sunulmaktadır. Güçlendirilmiş gövde ve yüksek kayış sayısı arazide mükemmel çekiş sağlarken, düşük yuvarlanma direnci daha iyi yakıt ekonomisine katkıda bulunur.

UM

US Standard

Construction

RADIAL

Machinery

Zirai: Yüksek güçte traktör

Version	HIGH SPEED
Type	TL
Tyre Size	540/65 R 38
LI/SS	153 D/150 E

Dimensions US Standard

Usa code	94044290
Section Width (inch)	20.9
Overall Diameter (inch)	65.6
Static Loaded Radius (inch)	30.3
Rolling Circumference (inch)	198.8
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000816
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	3470	3990	4590	5170	5760	6360	6880	7390
40	3790	4350	4990	5630	6280	6920	7480	8050
30	3980	4570	5250	5920	6600	7270	7870	8450
25	4140	4760	5470	6170	6880	7580	8200	8820
15	4500	5160	5920	6690	7450	8210	8880	9550
5	5680	6530	7480	8450	9420	10380	11230	12070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 6:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..