

AGRIMAX SPARGO - Teknik Özellikler



Description

AGRIMAX SPARGO, ürün arası uygulamaları için özel BKT lastiğidir. Tarlalarda gelişmiş üretkenlik ve uzun vadede toprağın korunması için tasarlanmıştır. VF teknolojisi sayesinde lastik, standart basınçta daha yüksek yük kapasitesi sağlar. Güçlü gövdesi ve daha yüksek diş sayısı sayesinde AGRIMAX SPARGO, hem tarlalarda hem de yol transferlerinde güçlü sabitleme ile birlikte olağanüstü dayanıklılık sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 46
LI/SS	165 D

Dimensions US Standard

Usa code	94075645
Section Width (inch)	12.7
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	31.9
Rolling Circumference (inch)	209.3
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-0010077
TRA Code	R1

Load capacity (lbs)

mph / psi	15	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	4520	5050	5680	6210	6520	6840	7050	7260	7620	8000	8300	8620	8890	9150	9410	9670	10090	10510
From 40 to 25	4890	5460	6140	6710	7050	7390	7620	7840	8240	8640	8980	9320	9610	9890	10170	10450	10910	11360
20	4990	5570	6270	6850	7190	7540	7780	9010	8400	8810	9160	9510	9800	10090	10380	10660	11130	11590
12	5090	5680	6390	6980	7330	7690	7930	8160	8580	8990	9340	9700	9990	10290	10590	10880	11360	11820
5	5380	6000	6750	7380	7750	8130	8380	8620	9070	9510	9880	10260	10560	10870	11190	11500	12000	12490

Printed on 4/27/2024 11:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..