

AGRIMAX SPARGO - Teknik Özellikler



Description

AGRIMAX SPARGO, ürün arası uygulamaları için özel BKT lastiğidir. Tarlalarda gelişmiş üretkenlik ve uzun vadede toprağın korunması için tasarlanmıştır. VF teknolojisi sayesinde lastik, standart basınçta daha yüksek yük kapasitesi sağlar. Güçlü gövdesi ve daha yüksek diş sayısı sayesinde AGRIMAX SPARGO, hem tarlalarda hem de yol transferlerinde güçlü sabitleme ile birlikte olağanüstü dayanıklılık sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 50
LI/SS	169 D

Dimensions US Standard

Usa code	94069545
Section Width (inch)	12.7
Overall Diameter (inch)	72.7
Static Loaded Radius (inch)	34.1
Rolling Circumference (inch)	222.4
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-007204
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64	70
45	5330	5920	6520	6810	7100	7350	7580	7930	8290	8400	8530	9050	9590	9830	10070	10530	11010	11830
From 40 to 25	5760	6400	7040	7360	7680	7940	8190	8580	8960	9090	9220	9790	10370	10620	10870	11390	11900	12790
20	5880	6530	7190	7510	7840	8110	8360	8760	9140	9270	9410	9990	10590	10840	11100	11620	12150	13060
12	6000	6660	7320	7670	8000	8260	8530	8920	9320	9450	9590	10190	10790	11050	11310	11850	12380	13310
5	6340	7040	7740	8100	8450	8730	9010	9430	9860	9990	10130	10770	11400	11690	11960	12530	13090	14070

Printed on 4/28/2024 4:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..