

AGRIMAX SPARGO - Teknik Özellikler



Description

AGRIMAX SPARGO, ürün arası uygulamaları için özel BKT lastiğidir. Tarlalarda gelişmiş üretkenlik ve uzun vadede toprağın korunması için tasarlanmıştır. VF teknolojisi sayesinde lastik, standart basınçta daha yüksek yük kapasitesi sağlar. Güçlü gövdesi ve daha yüksek diş sayısı sayesinde AGRIMAX SPARGO, hem tarlalarda hem de yol transferlerinde güçlü sabitleme ile birlikte olağanüstü dayanıklılık sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama

Version	STANDARD
Type	TL
Tyre Size	VF 480/80 R 46
LI/SS	177 D

Dimensions US Standard

Usa code	94057306
Section Width (inch)	18.9
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	35.1
Rolling Circumference (inch)	232.6
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-004756
TRA Code	R1

Load capacity (lbs)

mph / psi	17	20	23	26	29	32	35	38	41	44	47	49	52
45	8190	9080	9960	10390	10980	11270	11570	12150	12740	13180	13760	14200	14640
from 40 to 25	9010	9980	10940	11420	12070	12390	12710	13350	14000	14490	15130	15610	16100
20	9190	10180	11160	11660	12310	12640	12970	13620	14280	14780	15430	15920	16420
12	9370	10380	11380	11880	12550	12880	13220	13880	14550	15060	15720	16230	16740
5	9910	10970	12040	12570	13280	13630	13980	14690	15400	15930	16640	17170	17710

Printed on 4/28/2024 5:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..