

AGRIMAX TURF RT 333 - Teknik Özellikler



Description

AGRIMAX TURF RT 333 (R-3+); bahçe işlerinde ve üzüm bağları ile meyve bahçelerindeki uygulamalarda kullanılan küçük traktörler için tasarlanmış olan bir radyal lastiktir. Yuvarlak omuz tasarımı, daha az toprak sıkışması ile zemine son derece hassas davranmasını sağlar. Benzersiz ekstra derin sırtı (R-3+) ve yönlü bloklarla hazırlanmış özel tasarımı, hem arazide hem de yolda mükemmel çekiş ve daha uzun lastik kullanım ömrü sağlar. AGRIMAX TURF RT 333 (R-3+), olağanüstü kendi kendini temizleme özelliklerine sahiptir ve düşük yuvarlanma direnci sayesinde önemli miktarda yakıt tasarrufu sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Meyve hasadı makinesi • Küçük Traktör • Üzüm hasat makinesi

Version	STANDARD
Type	TL
Tyre Size	420/85 R 24
LI/SS	137 A8 / 137 B

Dimensions International Standard

Section Width (mm)	435
Overall Diameter (mm)	1324
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	3957
SRI (mm)	625
Rim Rec	W 15 L
Rim Alt	DW15L;DW14L
ECE	E11-106R-0010344

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1265	1475	1680	1890	2095	2300
40	1265	1475	1680	1890	2095	2300
30	1360	1580	1800	2025	2245	2465
10 LT	1700	1975	2255	2530	2810	3085
10 HT	1360	1580	1800	2025	2245	2465

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 03/05/2025 12:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..