

AGRIMAX TURF RT 333 - Veri Sayfasını İndir



Description

AGRIMAX TURF RT 333 (R-3+); bahçe işlerinde ve üzüm bağları ile meyve bahçelerindeki uygulamalarda kullanılan küçük traktörler için tasarlanmış olan bir radyal lastiktir. Yuvarlak omuz tasarımı, daha az toprak sıkışması ile zemine son derece hassas davranmasını sağlar. Benzersiz ekstra derin sırtı (R-3+) ve yönlü bloklarla hazırlanmış özel tasarımı, hem arazide hem de yolda mükemmel çekiş ve daha uzun lastik kullanım ömrü sağlar. AGRIMAX TURF RT 333 (R-3+), olağanüstü kendi kendini temizleme özelliklerine sahiptir ve düşük yuvarlanma direnci sayesinde önemli miktarda yakıt tasarrufu sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Meyve hasadı makinesi • Küçük Traktör • Üzüm hasat makinesi

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
220/55 R12	STANDARD	94070237		82 A8/B	W7		8.7	21.7	9.8	64.8	TL	E11-106R-007600
240/60 R12	STANDARD	94070657		89 A8/B	W7		9.5	23.3	10.6	70	TL	E11-106R-007679
200/65 R16	STANDARD	94070640		94 A8/B	W6		8	26.2	12.2	78.7	TL	E11-106R-007678
200/70 R 16	STANDARD	94074136	R1W	94 A8/B	W 6		7.9	27	12.5	80.9	TL	E11-106R-008659
240/70 R16	STANDARD	94070282		104 A8/B	W8	W 8 L ; W 9	9.6	29.2	13.4	87.1	TL	E11-106R-007531
260/70 R 16	STANDARD	94067909		109 A8/109 B	W 8	W 8 L ; W 9	10.2	30.3	13.7	90	TL	E11-106R-007158
280/70 R 16	STANDARD	94065714		112 A8/112 B	W9	W 8 ; W 10	11.4	31.5	14.1	93.3	TL	E11-106R-006472
280/70 R 18	STANDARD	94065707		114 A8/114 B	W 9	W 8 ; W 10	11.4	33.1	15.4	100.4	TL	E11-106R-006473
320/65 R 18	STANDARD	94071081		109 A8/109 B	W 10	W 9 ; W 11	12.6	34.4	15.5	102	TL	E11-106R-007844
300/70 R 20	STANDARD	9406748		110 A8/110 B	W9	W10	11.6	37.5	17	111.3	TL	E11-106R-006943
320/70 R 20	STANDARD	94067558		113 A8/113 B	W10	W9 ; W11	12.6	38.7	17.4	114.8	TL	E11-106R-006944
380/70 R 20	STANDARD	94068821		122 A8/122 B	W 12	W 11 ; W 13	15	42.6	19.1	126.5	TL	E11-106R-007111
360/70 R 24	STANDARD	94067916		122 A8/122 B	W 11	W 10 ; W 12	14.1	45.4	20.4	134.2	TL	E11-106R-007110
380/70 R 24	STANDARD	94068838		125 A8/125 B	W 12	W 11 ; W 13	15	46.9	21	139.3	TL	E11-106R-007112
420/70 R 24	STANDARD	94069460		130 A8 / 130 B	W 13	W 12 ; W 14 L	16.5	49.1	21.9	146.8	TL	E11-106R-007206
480/70 R 28	STANDARD	94075393		140 A8 / 140 B	W 15 L	W 14 L ; W 16 L	18.9	55.9	24.8	166.5	TL	E11-106R-009049
480/70 R 30	STANDARD	94075409		141 A8 / 141 B	W 15 L	W 14 L ; W 16 L	18.9	58.2	26	173.1	TL	E11-106R-009050
480/70 R 34	STANDARD	94075232		149 A8 / 149 B	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.5	188.4	TL	E11-106R-009042

Printed on 4/20/2024 9:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..