

AGRIMAX V-FLECTO - Teknik Özellikler



Description

AGRIMAX V-FLECTO, BKT'nin yüksek güçlü traktörlerde zorlu teknoloji ve performans talebine verdiği yanıtıdır. Bu lastik, daha az toprak sıkışması ve kendi kendini temizleme özellikleri sayesinde toprak işleme ve taşıma uygulamaları için mükemmeldir. Yenilikçi VF teknolojisi ile AGRIMAX V-FLECTO, standart ve IF lastiklere kıyasla daha düşük bir şişirme basıncıyla ağır yükleri taşıyıp yüksek hızlara ulaşabilir. Ayrıca, lastik üzerine standart jantların monte edilmesini sağlayan Dar Jant Seçeneğine sahiptir. BKT, bu lastiği hem tarlada hem de yolda sürüş konforunu artırmak için, yakıt tüketimini azaltan, optimize edilmiş geometri ile tasarladı.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Yüksek güçte traktör

Version	STANDARD
Type	TL
Tyre Size	VF 710/75 R 38
LI/SS	183 D

Dimensions US Standard

Usa code	94066339
Section Width (inch)	28.3
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	35.6
Rolling Circumference (inch)	242.2
Rim Rec	DW 24 B
Rim Alt	DW 23 B ; DW 25 B
ECE	E11-106R-006764
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	8770	10170	11580	13150	14560	15960	17550
From 40 to 25	9640	11190	12730	14460	16000	17550	19290
20	9830	11410	12980	14750	16320	17890	19680
12	10030	11630	13240	15030	16640	18240	20060
5	10600	12300	14000	15910	17600	19300	21220
*Upto 5 Cyc with front loader	13500	15660	17820	20240	22400	24560	27010
5 HT	9830	11410	12980	14750	16320	17890	19680

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 11:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..