

## AGRIMAX V-FLECTO - Teknik Özellikler



### Description

AGRIMAX V-FLECTO, BKT'nin yüksek güçlü traktörlerde zorlu teknoloji ve performans talebine verdiği yanıttır. Bu lastik, daha az toprak sıkışması ve kendi kendini temizleme özellikleri sayesinde toprak işleme ve taşıma uygulamaları için mükemmeldir. Özel VF teknolojisi ile AGRIMAX V-FLECTO, standart ve IF lastiklere kıyasla daha düşük bir şişirme basıncıyla ağır yükleri taşıyıp yüksek hızlara ulaşabilir. Ayrıca, lastik üzerine standart jantların monte edilmesini sağlayan Dar Jant Seçeneğine sahiptir. BKT, bu lastiği hem tarlada hem de yolda sürüş konforunu artırmak için, yakıt tüketimini azaltan, optimize edilmiş geometri ile tasarladı.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Yüksek güçte traktör

Version	STANDARD
Type	TL
Tyre Size	VF900/60 R 38 NRO
LI/SS	187 D

## Dimensions US Standard

Usa code	94075096
Section Width (inch)	34.7
Overall Diameter (inch)	80.5
Static Loaded Radius (inch)	34.7
Rolling Circumference (inch)	238.3
Rim Rec	DW 30 B
Narrow Rim option	DW 27 B
ECE	E11-106R-009004
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	9580	11140	12910	14470	16040	17600	19550
From 40 to 25	10530	12250	14190	15910	17620	19340	21490
20	10740	12490	14460	16210	17970	19730	21920
12	10950	12730	14750	16530	18320	20120	22350
5	11570	13470	15600	17490	19380	21270	23640
*Upto 5 Cyc with front loader	14740	17140	19850	22270	24670	27080	30090
5 HT	10740	12490	14460	16210	17970	19730	21920

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 4/19/2024 12:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..