

AIROMAX AM 27 - Teknik Özellikler



Description

AIROMAX AM 27 vinçlerin kullanıldığı inşaat uygulamaları için yola yönelik ideal lastiktir. Isıya karşı olağanüstü dayanıklılık ve sıra dışı sürüş konforu sağlar. AIROMAX AM 27 özellikle yüksek seviyede yol tutuş niteliği gerektiren işler için uygun, yüksek hızlı bir lastiktir.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Mobil Vinç

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 F

Dimensions US Standard

Usa code	94044214
Overall Width (inch)	14.6
Overall Diameter (inch)	53.7
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	164.4
Rim Rec	10.00/1.5
ECE	E11-54R-0015911

Load capacity (lbs)

mph / psi	130
50	13200

Printed on 2/26/2024 2:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..