

## AIROMAX AM 543 - Teknik Özellikler



### Description

AIROMAX AM 543 vinçlerin kullanıldığı inşaat uygulamaları için ideal lastiktir. Sıra dışı çekiş ve yüksek seviyede istikrar sağlar. Vinç lastikleri daha fazla baskıya ve zorlayıcı kullanım koşullarına maruz kaldıkları için, AIROMAX AM 543 ısıya karşı kusursuz dayanıklılık sağlamak üzere tasarlanmıştır. Bunun yanında, yüksek seviyede yol tutuşu gerektiren tüm işlemler için uygundur.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Endüstriyel: Mobil Vinç

Version	STANDARD
Type	TT
Tyre Size	385/95 R 24 (14.00 R 24)
LI/SS	170 E

## Dimensions International Standard

Overall Width (mm)	375
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4156
Rim Rec	10.00W

## Load capacity (Kg)

km/h / bar	9.00
70	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 12:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..