

AIROMAX AM 543 - Veri Sayfasını İndir

Description

AIROMAX AM 543 vinçlerin kullanıldığı inşaat uygulamaları için ideal lastiktir. Sıra dışı çekiş ve yüksek seviyede istikrar sağlar. Vinç lastikleri daha fazla baskıya ve zorlayıcı kullanım koşullarına maruz kaldıkları için, AIROMAX AM 543 ısıya karşı kusursuz dayanıklılık sağlamak üzere tasarlanmıştır. Bunun yanında, yüksek seviyede yol tutuşu gerektiren tüm işlemler için uygundur.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Mobil Vinç



SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
385/95 R 24 (14.00 R 24)	STANDARD	94064502	170 E	10.00W		14.8	53.3	24.7	163.6	TT
385/95 R 25 (14.00 R 25)	STANDARD	94064519	170 E	10.00/1.5		14.8	53.3	24.7	163.6	TL
445/95 R 25 (16.00 R 25)	STANDARD	94036660	177 E	11.25/2.0	11.00/1.7 CR ; 11.00/1.7CRL	17.1	58.3	26.4	177.2	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 12:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..