

ARROW - Teknik Özellikler



Description

ARROW römork kullanılan taşıma uygulamaları için uygundur. Yakıttan tasarruf ve daha uzun kullanım ömrü sağlayan yol odaklı bir lastiktir. ARROW, yüksek hızlarda da yüksek yük kapasitesine sahiptir. Ayrıca, geliştirilmiş performans gerektiren kullanıcılar için özel hamurlu HD versiyonu mevcuttur.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Römork

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions US Standard

Usa code	94022472
Ply Rating	16
Section Width (inch)	11.3
Overall Diameter (inch)	42.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (lbs)

	mph / psi	-	-
	-	-	-
	-	-	-

Printed on 4/25/2024 11:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..