

AS 2001 - Teknik Özellikler



Description

AS 2001, toprak işleme operasyonlarında traktörlere en iyi şekilde uyan çapraz katlı bir lastiktir. Tasarımı mükemmel çekiş ve kendi kendini temizleme özellikleri sağlar. AS 2001, aynı zamanda mükemmel yük kapasitesi sağlayan, kesilme ve kopmaya dirençli özel bir hamurdan yapılmıştır.

UM

US Standard

Construction

❖ BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	131 A8

Dimensions US Standard

Usa code	94002689
Ply Rating	8
Section Width (inch)	16.9
Overall Diameter (inch)	55.9
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	170
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-003508
TRA Code	R1

Load capacity (lbs)

	mph / psi	24
	25	4300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/13/2025 5:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..