

AS 504 - Teknik Özellikler



Description

AS 504, temel olarak toprak işleme, uygulama ve malzeme elleçleme işlemleri için tasarlanmış, tarımsal sanayi amaçlı bir lastiktir. Mükemmel kendi kendini temizleme özellikleri ve daha iyi kavrama özelliklerine sahip olan bu lastik, tarla römorkları ve teleskopik yükleyiciler için uygundur. AS 504, belirli son kullanıcı gereksinimlerini karşılamak için çeşitli versiyonlarda sunulmaktadır: kesilme ve kopmaya karşı dirençli özel bir hamura sahip "HD" versiyonu ve daha uzun lastik ömrü sağlayan güçlendirilmiş gövdeye sahip "özel" versiyon.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Teleskopik yükleyici • Tarla römorku
Endüstriyel: Teleskopik yükleyici

Version	SPECIAL
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	308
Overall Diameter (mm)	987
Static Loaded Radius (mm)	438
Rolling Circumference (mm)	2892
SRI (mm)	475
Rim Rec	W 9
Rim Alt	9 ; 11
ECE	E11-106R-004346

Load capacity (Kg)

	km/h / bar	3.70
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650
	10 DW	2590
	25 DW	2200
	30 DW	2070
	40 DW	1850

Printed on 4/25/2024 11:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..