

## AS 504 - Teknik Özellikler



### Description

AS 504, temel olarak toprak işleme, uygulama ve malzeme elleçleme işlemleri için tasarlanmış, tarımsal sanayi amaçlı bir lastiktir. Mükemmel kendi kendini temizleme özellikleri ve daha iyi kavrama özelliklerine sahip olan bu lastik, tarla römorkları ve teleskopik yükleyiciler için uygundur. AS 504, belirli son kullanıcı gereksinimlerini karşılamak için çeşitli versiyonlarda sunulmaktadır: kesilme ve kopmaya karşı dirençli özel bir hamura sahip "HD" versiyonu ve daha uzun lastik ömrü sağlayan güçlendirilmiş gövdeye sahip "özel" versiyon.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Teleskopik yükleyici • Tarla römorku  
Endüstriyel: Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	27 X 10 - 15.3
LI/SS DRIVE WHEEL	95 A8
LI/SS FREE ROLLING	107 A8

## Dimensions US Standard

Usa code	94039500
Ply Rating	8
Section Width (inch)	10.2
Overall Diameter (inch)	27.4
Static Loaded Radius (inch)	12.5
Rolling Circumference (inch)	81.5
Rim Rec	9.00
ECE	E4-106R-002324

## Load capacity (lbs)

mph / psi	45
5 FR	3010
15 FR	2560
20 FR	2400
25 FR	2150
5 DW	2130
15 DW	1810
20 DW	1710
25 DW	1520

Printed on 4/25/2024 9:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..