

## AS 504 - Teknik Özellikler



### Description

AS 504, temel olarak toprak işleme, uygulama ve malzeme elleçleme işlemleri için tasarlanmış, tarımsal sanayi amaçlı bir lastiktir. Mükemmel kendi kendini temizleme özellikleri ve daha iyi kavrama özelliklerine sahip olan bu lastik, tarla römorkları ve teleskopik yükleyiciler için uygundur. AS 504, belirli son kullanıcı gereksinimlerini karşılamak için çeşitli versiyonlarda sunulmaktadır: kesilme ve kopmaya karşı dirençli özel bir hamura sahip "HD" versiyonu ve daha uzun lastik ömrü sağlayan güçlendirilmiş gövdeye sahip "özel" versiyon.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Teleskopik yükleyici • Tarla römorku  
Endüstriyel: Teleskopik yükleyici

Version	HD
Type	TT
Tyre Size	7.50 - 16
LI/SS DRIVE WHEEL	99 A8
LI/SS FREE ROLLING	112 A8

## Dimensions US Standard

Usa code	94043026
Ply Rating	8
Section Width (inch)	8.2
Overall Diameter (inch)	31.6
Static Loaded Radius (inch)	14.6
Rolling Circumference (inch)	97.4
Rim Rec	5.50 F
Rim Alt	4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F
ECE	E11-106R-004337

## Load capacity (lbs)

mph / psi	46
5 FR	3460
15 FR	2940
20 FR	2770
25 FR	2470
5 DW	2390
15 DW	2030
20 DW	1920
25 DW	1710

Printed on 4/25/2024 6:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..