

## AS 511 - Teknik Özellikler

### Description

AS 511, uygulamalı makinelerle çim daha operasyonları için en uygundur. Sağlam gövde ve kesilmeye dirençli özel sırt hamuru, olağanüstü sabitlemenin yanı sıra gelişmiş performans sağlar. Geniş temas alanı sayesinde AS 511, mükemmel çekiş sağlar ve toprak sıkışmasını en aza indirir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Uygulamalı makine



|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 31 X 15.50 R 15 |
| LI/SS     | 122 B           |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 388             |
| Overall Diameter (mm)      | 785             |
| Static Loaded Radius (mm)  | 353             |
| Rolling Circumference (mm) | 2387            |
| SRI (mm)                   | 380             |
| Rim Rec                    | 13 LB           |
| ECE                        | E11-106R-005098 |

## Load capacity (Kg)

| km/h / bar | 2.8  |
|------------|------|
| 50         | 1500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 6:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..