

AT 108 - Teknik Özellikler



Description

AT 108, ATV'ler için her araziye uygun bir lastiktir. Sırt tasarımı, hem yolda hem de yol dışında mükemmel konfor ve performans sağlar.

UM

International Standard

Construction



Machinery

Zirai: ATV

| Version | STANDARD |
|-----------|----------------|
| Туре | TL |
| Tyre Size | AT 22 X 8 - 10 |

Dimensions International Standard

| Ply Rating | 6 |
|-----------------------|-------------------|
| Section Width (mm) | 206 |
| Overall Diameter (mm) | 557 |
| Rim Rec | 6.5 AT |
| Rim Alt | 6.0 AT |
| ECE | E4-75R-0004981-01 |

Load capacity (Kg)

| km/h / bar | 0.45 |
|------------|------|
| 100 | 125 |

Printed on 4/29/2024 10:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..