

## AT 108 - Teknik Özellikler



### Description

AT 108, ATV'ler için her araziye uygun bir lastiktir. Sırt tasarımı, hem yolda hem de yol dışında mükemmel konfor ve performans sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: ATV

Version	STANDARD
Type	TL
Tyre Size	AT 25 X 13 - 9

# Dimensions International Standard

Ply Rating	6
Section Width (mm)	320
Overall Diameter (mm)	635
Rim Rec	10.5 AT
Rim Alt	10.0 AT
ECE	E11-75R-004656

## Load capacity (Kg)

km/h / bar	0.45
100	243

Printed on 4/29/2024 4:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..