

AT 111 HD - Teknik Özellikler



Description

AT 111 HD, ATV'lerle her arazide spor yarışı için uygundur. Arttırılmış diş derinliği ve kalın yanak, güç kızaklarında olağanüstü çekiş ve yüksek hız kontrolüne ek olarak ekstra kavrama ve fren kontrolü sağlar. AT 111 HD, uzun lastik kullanım ömrü sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: ATV

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | AT 22 X 11 - 10 |

Dimensions International Standard

| | |
|-----------------------|----------------|
| Ply Rating | 6 |
| Section Width (mm) | 279 |
| Overall Diameter (mm) | 560 |
| Rim Rec | 9.0 AT |
| Rim Alt | 8.5 AT |
| ECE | E4-75R-0006333 |

Load capacity (Kg)

| km/h / bar | 0.45 |
|------------|------|
| 100 | 175 |

Printed on 4/25/2024 8:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..