

AT 171 - Teknik Özellikler



Description

AT 171 özellikle çamur bataklık traktörleri için tasarlanmıştır. Özel yönlü ve ekstra derin sırt tasarımı ıslak ve çamurlu yüzeylerde mükemmel çekiş sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: ATV • Çamur bataklık traktörü

Version	STANDARD
Type	TL
Tyre Size	AT 35 X 9 - 22
LI/SS	88 A8/ 64 F

Dimensions International Standard

Ply Rating	6
Section Width (mm)	210
Overall Diameter (mm)	890
Rim Rec	W7
Rim Alt	W6
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	1.40	1.00
40 MUD BOGGING	560	-
80 MUD BOGGING	280	-
40 CASUAL TRANSPORT	-	455
80 CASUAL TRANSPORT	-	230

Printed on 5/5/2024 12:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..