

AT 316 - Teknik Özellikler



Description

AT 316, şehircilik ve bakım uygulamalarında kullanılan hizmet tipi kompakt traktörler için uygundur. Özel diş tasarımı arazi korumasından taviz vermeden kusursuz çekiş sağlar; bu da bu tür uygulamalar için vazgeçilmez bir özelliktir. AT 316, delinmelere karşı daha fazla dayanıklılık için "aramid kuşaklı" modeliyle de mevcuttur.

UM

International Standard

Construction

❖ BIAS

Machinery

Zirai: Küçük hizmet traktörü

Version	STANDARD
Type	TL
Tyre Size	24 X 12.00 - 12

Dimensions International Standard

Ply Rating	4
Section Width (mm)	315
Overall Diameter (mm)	610
Static Loaded Radius (mm)	271
Rolling Circumference (mm)	1769
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-004082

Load capacity (Kg)

km/h / bar	1.40
15	775

Printed on 4/17/2024 6:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..