

## AT 316 - Teknik Özellikler



### Description

AT 316, şehircilik ve bakım uygulamalarında kullanılan hizmet tipi kompakt traktörler için uygundur. Özel diş tasarımı arazi korumasından taviz vermeden kusursuz çekiş sağlar; bu da bu tür uygulamalar için vazgeçilmez bir özelliktir. AT 316, delinmelere karşı daha fazla dayanıklılık için "aramid kuşaklı" modeliyle de mevcuttur.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Zirai: Küçük hizmet traktörü

Version	ARAMID BELTED
Type	TL
Tyre Size	24 X 12.00 - 12

## Dimensions US Standard

Usa code	94001217
Ply Rating	6
Section Width (inch)	12.4
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.7
Rolling Circumference (inch)	69.6
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90

## Load capacity (lbs)

mph / psi	32
10	2270

Printed on 4/17/2024 5:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..